

FRENCH INTERIM MALE UAV PROGRAM



4


INDUSTRIAL STATUS

June, 13th 2002

Report Documentation Page			Form Approved OMB No. 0704-0188		
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 02 SEP 2003		2. REPORT TYPE N/A		3. DATES COVERED -	
4. TITLE AND SUBTITLE French Interim Male UAV Program				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) EADS-S&DE, France				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES See also ADM001676, UAV 2002 Conference & Exhibition., The original document contains color images.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 17	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			



ISR systems activities localisation in the EADS organisation



Systems and Defence Electronics includes the former UAV activities from Aerospatiale, Matra, DASA and CAC Systems

June, 13th 2002



**EADS S&DE-ISR delivers turnkey solutions
for intelligence surveillance and reconnaissance purposes.**

ISR
Intelligence, Surveillance & Reconnaissance


SYSTEMS



**GROUND
SEGMENTS**




GEOMATICS



June, 13th 2002



**EADS S&DE-ISR delivers turnkey solutions
 for intelligence surveillance and reconnaissance purposes.**



June, 13th 2002



**EADS S&DE-ISR delivers turnkey solutions
for intelligence surveillance and reconnaissance purposes.**

OPERATIONAL MISSIONS COVERED

**GROUND SURVEILLANCE
AEW (Airborne Early Warning)
AIRBORNE COMMAND & CONTROL
ELECTRONIC WARFARE
RELAY
SPECIAL OPERATIONS
FLYING TEST BEDS
ACTD (feasibility demonstrations)**

**THE BEST SYSTEM
AT THE RIGHT TIME
DEDICATED TO THE
CUSTOMER & HIS BUDGET**

**MANNED AND/OR UNMANNED AIRBORNE SYSTEMS +
ASSOCIATED GROUND SUB-SYSTEMS (HW,SW)
SENSORS (FROM EADS OR PARTNERS)
FIXED OR MOBILE SATELLITE RECEPTION STATIONS**

June, 13th 2002



EADS S&DE-ISR delivers the Eagle system to FAF

System capabilities



AUTONOMY : + 24 h, or 18 hours at 1000 km @ 15000 feet with mission payload to achieve :

IMINT Missions

- All Weather Surveillance
- All Weather Reconnaissance
- Battle Management
- Battle Damage Assessment

Support Missions

- Radio Relay
- Target designation / illumination


MISSION RELIABILITY : Over 100 000 hours between two uncontrolled losses.

June, 13th 2002



EADS S&DE-ISR delivers the Eagle system to FAF

Air Vehicle characteristics



Max Take-off weight	1150 kg
Max. Payload capacity	250 kg
Max. Fuel capacity	300 kg
Max altitude	32 000 ft
Operational altitude	> 20 000 ft
Time of climb	50 mn (20 kft)
Max speed	125 ktas
Cruise speed at OA	90 ktas
Total mission time	30 h
Loiter capability at 550 NM	18 h
Maximum range (1 h loiter)	1700 nm


June, 13th 2002



EADS S&DE-ISR delivers the Eagle system to FAF

Safety integrated system

Safety equipments for airspace integration:
IFFmode S, ATC radio relay, Backups, and
piloting camera.



Fail safe avionics approach :


Redundancies, fail safe
architecture and rerouting
capability in case of major
failure (Flight termination
system).

June, 13th 2002



EADS S&DE-ISR delivers the Eagle system to FAF

EO/IR/LR COTS Payload



Turret already in production :





- EO (20-280 and 55-770 mm)
- IR (32, 150 and 600 mm)
- Laser (stabilisation => + 8km)

June, 13th 2002




EADS S&DE-ISR delivers the Eagle system to FAF

SAR COTS Payload



Strip mode



GMTI
mode



Spot mode

Range: > 30 Km in adverse conditions
Resolution: up to 30cm
Modes: strip, spot, MTI

June, 13th 2002




EADS S&DE-ISR delivers the Eagle system to FAF

COTS Avionics + innovative developments



MPCA*
(Modular Central
Processing Assembly)




Data Manager*



Radio relay*



Recorder*



INS/GPS*



IFF*




** pictures only for illustration, without contractual aspects*

June, 13th 2002



EADS S&DE-ISR delivers the Eagle system to FAF

OTS SATCOMM + innovative developments




** pictures only for illustration, without contractual aspect*

June, 13th 2002



EADS S&DE-ISR delivers the Eagle system to FAF


COTS LOS Data-Link



** pictures only for illustration, without contractual aspect*

June, 13th 2002

SYSTEM ARCHITECTURE




EADS
European Aeronautic Defence and Space Company

Lcl Monsterleet FAF Staff
J. Caron EADS S&DE-ISR



EADS S&DE-ISR delivers the Eagle system to FAF



Example of smart system function : the “camera guided” mode

- The trajectory of the aerial vehicle is slaved to the EO/IR camera in order to track continuously the selected target
- This mode allows the operator to focus on the monitor by controlling only the EO/IR payload.
- When the selected target is fixed, the aerial vehicle will hold around the target or at a predefined offset from this target.
- When the selected target is on the move, the aerial vehicle will automatically track the moving target either above or at a predefined offset from this target.

June, 13th 2002



EADS S&DE-ISR delivers the Eagle system to FAF



June, 13th 2002



More questions ?

June, 13th 2002